

SEWAGE PUMPS
SW50 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SW50M1-20	1/2	60	115/1	3450	9.5	P	SJTOW	16 AWG/3C	.36	N/A	N/A	250V 20MFD±5%
SW50M2-20	1/2	60	230/1	3450	4.8	P	SJTOW	16 AWG/3C	.36	N/A	N/A	250V 20MFD±5%
SW50M3-20	1/2	60	230/3	3450	3.0	R	SJTOW	16 AWG/4C	.36	N/A	N/A	250V 20MFD+5%
SW50M5-20	1/2	60	208/1	3450	5.2	P	SJTOW	16 AWG/3C	.36	N/A	N/A	250V 20MFD+5%
SW50M6-20	1/2	60	208/3	3450	3.1	R	SJTOW	16 AWG/4C	.36	N/A	N/A	250V 20MFD+5%

MOTOR TYPE	PSC
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com