

SOLIDS HANDLING PUMPS  
**3ANC750 Technical Data**

**Physical Data:**

DISCHARGE SIZE	3"
IMPELLER TYPE	Single Vane Enclosed
CABLE LENGTH	35'

**Liquid Handling:**

MAXIMUM LIQUID TEMP.	140°F – Intermittent 104°F - Continuous
ACCEPTABLE PH RANGE	6-8

**Temperature:**

MAXIMUM STATOR	155°C
----------------	-------

**Technical Data:**

POWER CORD TYPE	S00W
SENSOR CORD TYPE	S00W
MOTOR HOUSING	Cast Iron
CASING	Cast Iron
IMPELLER	Cast Iron
MOTOR SHAFT	410 SS
HARDWARE	SST
“O” RINGS	Viton™
MECHANICAL SEALS	Inboard Mechanical Seal: Carbon-ceramic Outboard Mechanical Seal: Silicon Carbide
UPPER BEARING	6304
LOWER BEARING	6207

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
3ANC750M3	7.5	60	230/3	1750	21	K	S00W	10AWG	.72	N/A	N/A	N/A
3ANC750M4	7.5	60	460/3	1750	10.5	K	S00W	10AWG	.72	N/A	N/A	N/A



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805  
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com