

# SEWAGE PUMPS

## SWH500 Technical Data

### Physical Data:

DISCHARGE SIZE	3" NPT
IMPELLER TYPE	9-Vane Vortex - Cast Iron
CABLE LENGTH	20'

### Liquid Handling:

SOLIDS SIZE	3"
MAXIMUM LIQUID TEMP.	104°F – Intermittent
ACCEPTABLE PH RANGE	6-8

### Temperature:

WINDING INSULATION TEMP.	130°C
--------------------------	-------

### Technical Data:

POWER CORD TYPE	SOW 14AWG/3C, 16AWG/4C
MOTOR HOUSING	Cast Iron
CASING	Cast Iron
IMPELLER	Cast Iron
MOTOR SHAFT	SS416
HARDWARE	SS
"O" RINGS	NBR
MECHANICAL SEALS	Mechanical Carbon Ceramic
UPPER BEARING	6203
LOWER BEARING	6206

## Specifications

Model	HP	Hz	Volts/Ph	RPM	Full Load Amps	Nema Start Code	Cord Type	Cord Power Size	Cord O.D.
SWH500M2-20	5	60	230/1	1750	40.0	D	SOW	6AWG/4C	1.2
SWH500M3-20	5	60	230/3	1750	23.6	D	SOW	12AWG/4C	.7
SWH500M4-20	5	60	460/3	1750	11.8	D	SOW	12AWG/4C	.7
SWH500M5-20	5	60	208/1	1750	46.0	D	SOW	6AWG/4C	1.2
SWH500M6-20	5	60	208/3	1750	24.0	D	SOW	12AWG/4C	.70



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com