

SEWAGE PUMPS  
**SWF100 Electrical Data**

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWF100M2-20	1	60	230/1	15A	1750	10.8	P	SOW	14AWG/3C	.55	N/A	N/A	350V 35MFD±5%
SWF100M3-20	1	60	230/3	10A	1750	8.0	P	SOW	16AWG/4C	.45	N/A	N/A	N/A
SWF100M4-20	1	60	460/3	5A	1750	4.0	P	SOW	16AWG/4C	.45	N/A	N/A	N/A
SWF100M5-20	1	60	208/1	15A	1750	13.0	P	SOW	14AWG/3C	.55	N/A	N/A	N/A
SWF100M6-20	1	60	208/3	10A	1750	8.5	P	SOW	16AWG/3C	.45	N/A	N/A	N/A

MOTOR TYPE	PSC (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com