

GRINDER PUMPS
AGP300 Electrical Data

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
AGP300M2-35	3	60	230/1	32A	3450	23.1	G	SOW	12AWG/4C	.68	500V, 300 Pickup	108-130uF-250 VAC	30uF±5%-370VAC
AGP300M3-35	3	60	230/3	20A	3450	14.3	M	SOW	14AWG/4C	.59	N/A	N/A	N/A
AGP300M4-35	3	60	460/3	10A	3450	7.1	M	SOW	14AWG/4C	.59	N/A	N/A	N/A
AGP300M5-35	3	60	208/1	32A	3450	26	G	SOW	12AWG/4C	.68	500V, 300 Pickup	108-130uF-250 VAC	30uF±5%-370VAC
AGP300M6-35	3	60	208/3	20A	3450	14	M	SOW	14AWG/4C	.59	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Heat Sensors, Seal Leak Detection



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com