

GRINDER PUMPS  
**AGP750 Electrical Data**

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
AGP750M2-35	7.5	60	230/1	40A	3450	36.5	F	SOW	8AWG/4C	.96	500V, 300 Pickup	270-324uF-250 VAC	30uF±5%-370VAC
AGP750M3-35	7.5	60	230/3	32A	3450	24.6	K	SOW	8AWG/4C	.96	N/A	N/A	N/A
AGP750M4-35	7.5	60	460/3	20A	3450	12.3	K	SOW	8AWG/4C	.96	N/A	N/A	N/A
AGP750M5-35	7.5	60	208/1	40A	3450	38	F	SOW	8AWG/4C	.96	500V, 300 Pickup	270-324uF-250 VAC	30uF±5%-370VAC
AGP750M6-35	7.5	60	208/3	32A	3450	22	K	SOW	8AWG/4C	.96	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Heat Sensors, Seal Leak Detection



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com