

SOLIDS HANDLING PUMPS
ANC750 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
ANC750M2-35	7.5	60	230/1	1750	58.2	D	SOW	6AWG/4C	1.2	ICM CONTROLS UMSR-50-LF	161-193UF-220 VAC	15uF±5%-370VAC
ANC750M3-35	7.5	60	230/3	1750	30.8	E	SOW	8AWG/4C	1.05	N/A	N/A	N/A
ANC750M4-35	7.5	60	460/3	1750	15.4	E	SOW	8AWG/4C	1.05	N/A	N/A	N/A
ANC750M5-35	7.5	60	208/1	1750	60.0	D	SOW	6AWG/4C	1.2	ICM CONTROLS UMSR-50-LF	161-193UF-220 VAC	15uF±5%-370VAC
ANC750M6-35	7.5	60	208/3	1750	31.0	E	SOW	8AWG/4C	1.05	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
STATOR WINDING CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com