

SOLIDS HANDLING PUMPS
ANCV300 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
ANCV300M2-35	3	60	230/1	1750	19.3	G	SOW	12AWG/4C	.71	CONT. COIL VOLTAGE: 350V PICK-UP MAX. 200V DROP-OUT MAX. 75V	430-516UF-220VAC	30UF-370VAC
ANCV300M3-35	3	60	230/3	1750	13.2	K	SOW	14AWG/4C	.62	N/A	N/A	N/A
ANCV300M4-35	3	60	460/3	1750	6.6	K	SOW	14AWG/4C	.62	N/A	N/A	N/A
ANCV300M5-35	3	60	208/1	1750	22.0	G	SOW	12AWG/4C	.71	CONT. COIL VOLTAGE: 350V PICK-UP MAX. 200V DROP-OUT MAX. 75V	161-193UF-220 VAC	15uF±5%-370VAC
ANCV300M6-35	3	60	208/3	1750	14.0	K	SOW	14AWG/4C	.62	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
STATOR WINDING CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com