

SEWAGE PUMPS
SWF300 Electrical Data

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWF300M2-20	3	60	230/1	15A	1750	28.0	D	SOW	8AWG/4C	1.0	N/A	N/A	350V 35MFD±5%
SWF300M3-20	3	60	230/3	10A	1750	20.0	D	SOW	12AWG/4C	.7	N/A	N/A	N/A
SWF300M4-20	3	60	460/3	5A	1750	10.0	D	SOW	12AWG/4C	.7	N/A	N/A	N/A
SWF300M5-20	3	60	208/1	15A	1750	33.5	D	SOW	8AWG/4C	1.0	N/A	N/A	N/A
SWF300M6-20	3	60	208/3	10A	1750	18.0	D	SOW	12AWG/4C	.7	N/A	N/A	N/A

MOTOR TYPE	PSC
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	N/A



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com