

SEWAGE PUMPS  
**SWHD150 Electrical Data**

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWHD150M2-20	1-1/2	60	230/1	15A	3450	13.8	P	SOW	14AWG/3C	.58	N/A	N/A	N/A
SWHD150M3-20	1-1/2	60	230/3	10A	3450	7.6	P	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWHD150M4-20	1-1/2	60	460/3	10A	3450	3.8	P	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWHD150M5-20	1-1/2	60	208/1	10A	3450	15.0	P	SOW	14AWG/3C	.58	N/A	N/A	N/A
SWHD150M6-20	1-1/2	60	208/3	10A	3450	7.8	P	SOW	16AWG/4C	.46	N/A	N/A	N/A

MOTOR TYPE	PSC (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com