

SWH50 Electrical Data

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWH50M1-20	1/2	60	115/1	15A	3450	12.0	P	SOW	16AWG/3C	.43	N/A	N/A	450V 35MFD±5%
SWH50M2-20	1/2	60	230/1	10A	3450	6.0	P	SOW	16AWG/3C	.43	N/A	N/A	450V 35MFD±5%
SWH50M3-20	1/2	60	230/3	5A	3450	4	P	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWH50M4-20	1/2	60	460/3	3A	3450	2	P	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWH50M5-20	1/2	60	208/1	10A	3450	6.8	P	SOW	16AWG/3C	.43	N/A	N/A	450V 35MFD±5%
SWH50M6-20	1/2	60	208/3	5A	3450	4.2	P	SOW	16AWG/4C	.46	N/A	N/A	N/A

MOTOR TYPE	PSC (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com