

GRINDER PUMPS
AGP-HC200 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
AGP-HC200M5-35	2	60	208/1	3450	20	G	SOW	12 AWG	.65	CONSULT FACTORY		
AGP-HC200M5E-35	2	60	208/1	3450	20	G	SOW	12 AWG	.65	SAMUSCO ECS225P	MARS 11068	MARS 12248
AGP-HC200M6-35	2	60	208/3	3450	12	G	SOW	12 AWG	.65	N/A	N/A	N/A
AGP-HC200M2-35	2	60	230/1	3450	18	G	SOW	12 AWG	.6	CONSULT FACTORY		
AGP-HC200M2E-35	2	60	230/1	3450	18	G	SOW	12 AWG	.65	SAMUSCO ECS225P	MARS 11068	MARS 12248
AGP-HC200M3-35	2	60	230/3	3450	12	G	SOW	12 AWG	.65	N/A	N/A	N/A
AGP-HC200M4-35	2	60	460/3	3450	6	G	SOW	12 AWG	.65	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+/-10%
MOTOR PROTECTION	Heat Sensors



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com