

SEWAGE PUMPS
SWH150 Electrical Data

| MODEL | HP | HZ | VOLTS/PH | BREAKER SIZE | RPM | FULL LOAD AMPS | NEMA START CODE | CORD TYPE | CORD SIZE | CORD O.D. | POTENTIAL RELAY | START CAPACITOR | RUN CAPACITOR |
|-------------|-------|----|----------|--------------|------|----------------|-----------------|-----------|-----------|-----------|-----------------|-----------------|---------------|
| SWH150M2-20 | 1-1/2 | 60 | 230/1 | 15A | 3450 | 13.8 | P | SOW | 14AWG/3C | .58 | N/A | N/A | N/A |
| SWH150M3-20 | 1-1/2 | 60 | 230/3 | 10A | 3450 | 7.6 | P | SOW | 16AWG/4C | .46 | N/A | N/A | N/A |
| SWH150M4-20 | 1-1/2 | 60 | 460/3 | 10A | 3450 | 3.8 | P | SOW | 16AWG/4C | .46 | N/A | N/A | N/A |
| SWH150M5-20 | 1-1/2 | 60 | 208/1 | 20A | 3450 | 15.0 | P | SOW | 14AWG/3C | .58 | N/A | N/A | N/A |
| SWH150M6-20 | 1-1/2 | 60 | 208/3 | 10A | 3450 | 7.8 | P | SOW | 16AWG/4C | .46 | N/A | N/A | N/A |

| | |
|--------------------------------|----------------------------|
| MOTOR TYPE | PSC (1PH), INDUCTION (3PH) |
| GENERAL INSULATION CLASS | B |
| WINDING INSULATION TEMPERATURE | 130°C |
| VOLTAGE TOLERANCE | +10% |
| MOTOR PROTECTION | Thermally Protected |



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com