

SEWAGE PUMPS
SWHD500 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM LOAD AMPS	FULL START CODE	NEMA	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWHD500M2-20	5	60	230/1	1750	40.0	D	SOW	6AWG/4C	1.2	Continuous Coil Min Voltage: 400V Pick-up Max: 200V Drop Out Max: 80V	750uf+/-5%-220VAC	40uf+/-5%-370VAC
SWHD500M3-20	5	60	230/3	1750	23.6	D	SOW	12AWG/4C	.70	N/A	N/A	N/A
SWHD500M4-20	5	60	460/3	1750	11.8	D	SOW	12AWG/4C	.70	N/A	N/A	N/A
SWHD500M5-20	5	60	208/1	1750	46.0	D	SOW	6AWG/4C	1.2	Continuous Coil Min Voltage: 400V Pick-up Max: 200V Drop Out Max: 80V	750uf+/-5%-220VAC	40uf+/-5%-370VAC
SWHD500M6-20	5	60	208/3	1750	24.0	D	SOW	12AWG/4C	.70	N/A	N/A	N/A

MOTOR TYPE	CAPACITOR START//CAPACITOR RUN (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	N/A



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com