

GRINDER PUMPS

Technical Data: **AGP2H-HC200**

PHYSICAL DATA:

DISCHARGE SIZE	1-1/4" NPT, Optional 2" NPT Adapter
IMPELLER TYPE	7 Vane Semi Open (Dual Impellers)
CABLE LENGTH	35'

LIQUID HANDLING:

SOLIDS COMPOSITION	Domestic Wastewater w/Fibrous Solids
MAXIMUM LIQUID TEMP.	140°F – Intermittent 104°F – Continuous
ACCEPTABLE PH RANGE	6-8

TEMPERATURE:

MAXIMUM STATOR	145°C
INSULATION CLASS	H

TECHNICAL DATA:

POWER CORD TYPE	SOW, Quick Change
SENSOR CORD TYPE	SOW, Quick Change
MOTOR HOUSING	Cast Iron
CASING	Cast Iron
IMPELLER	Brass
MOTOR SHAFT	416 SS
HARDWARE	SS
"O" RINGS	Fluorocarbon
MECHANICAL SEALS	SiC
UPPER BEARING	6203
LOWER BEARING	3205
CUTTER	440C SS, Hardened
MOTOR WINDINGS	Copper



P U M P

Honest, Professional, Dependable

1191 Commerce Parkway, Ashland, Ohio 44805
Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com