

SEWAGE PUMPS

Electrical Data: **SWF100**

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	RUN CAPACITOR
SWF100M2-20	1	60	230/1	1750	10.8	D	SOW	14AWG/3C	.55	350V 35MFD±5%
SWF100M3-20	1	60	230/3	1750	8.0	D	SOW	16AWG/4C	.45	N/A
SWF100M4-20	1	60	460/3	1750	4.0	D	SOW	16AWG/4C	.45	N/A
SWF100M5-20	1	60	208/1	1750	13.0	D	SOW	14AWG/3C	.55	350V 35MFD±5%
SWF100M6-20	1	60	208/3	1750	8.5	D	SOW	16AWG/3C	.45	N/A

ELECTRICAL DATA:

MOTOR TYPE	PSC (1PH), Induction (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMP	130°C
VOLTAGE TOLERANCE	±10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1191 Commerce Parkway, Ashland, Ohio 44805
Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com