

GRINDER PUMPS

Electrical Data: **AGP750**

MODEL	HP	HZ	VOLTS /PH	RPM	FULL LOAD	NEMA START AMPS	CORD TYPE CODE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
AGP750M3-35	7.5	60	230/3	3450	24.6	K	SOW	8AWG/4C	.96	N/A	N/A	N/A
AGP750M4-35	7.5	60	460/3	3450	12.3	K	SOW	8AWG/4C	.96	N/A	N/A	N/A
AGP750M6-35	7.5	60	208/3	3450	22	K	SOW	8AWG/4C	.96	N/A	N/A	N/A

ELECTRICAL DATA:

R.P.M.	3450
MOTOR TYPE	Induction (3PH)
GEN INSULATION CLASS	H
STATOR WINDING CLASS	H
WINDING INSULATION TEMP	180°C
VOLTAGE TOLERANCE	±10%
HP	7.5
VOLTAGE	208/230/460
PHASE	3
SERVICE FACTOR	1.4



P U M P

Honest, Professional, Dependable

1191 Commerce Parkway, Ashland, Ohio 44805
 Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com