

GRINDER PUMPS

Electrical Data: **AGP-HC750**

MODEL	HP	HZ	VOLTS /PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
AGP-HC750M3-35	7.5	60	230/3	3450	27	G	W	8AWG/4C	N/A	N/A	N/A
AGP-HC750M4-35	7.5	60	460/3	3450	13.5	G	SOOW	12AWG/4C	N/A	N/A	N/A
AGP-HC750M6-35	7.5	60	208/3	3450	31.1	F	W	8AWG/4C	N/A	N/A	N/A

ELECTRICAL DATA:

R.P.M.	3450
MOTOR TYPE	Induction (3PH)
GEN INSULATION CLASS	H
STATOR WINDING CLASS	H
WINDING INSULATION TEMP	180°C
VOLTAGE TOLERANCE	±10%
HP	7.5
VOLTAGE	208/230/460
PHASE	3
SERVICE FACTOR	1.15



P U M P

Honest, Professional, Dependable

1191 Commerce Parkway, Ashland, Ohio 44805
Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com